

LOOKOUTS
COMMUNICATION
ESCAPE ROUTES
SAFETY ZONES

COUNTY OF VOLUSIA

SAFETY GRAM

Captain Barry G. Ellis
Safety Officer

June 1, 2005

HURRICANE SCENE SAFETY

Fire Related Hazards Present During and After a Tornado or Hurricane

- Leaking gas lines, damaged or leaking gas propane containers, and leaking vehicle gas tanks may explode or ignite.
- Debris can easily ignite, especially if electrical wires are severed.
- Pools of water and even appliances can be electrically charged.
- Generators are often used during power outages. Generators that are not properly used and maintained can be very hazardous.
- Alternative heating devices used incorrectly create fire hazards. Proper use and maintenance can decrease the possibility of a fire.
- Appliances that emit smoke or sparks should be repaired or replaced.

Chemical Safety

- Look for combustible liquids like gasoline, lighter fluid, and paint thinner that may have spilled. Thoroughly clean the spill and place containers in a well-ventilated area.
- Keep combustible liquids away from heat sources.

Electrical Safety

- Assume all wires on the ground are electrically charged. This includes cable TV feeds.
- Exposed outlets and wiring could present a fire and life safety hazard.
- Appliances that emit smoke or sparks should be repaired or replaced.
- Have a licensed electrician check your home for damage.

Gas Safety

- Smell and listen for leaky gas connections. If you believe there is a gas leak, immediately leave the house and leave the door (s) open.

Generator Safety

- Follow the manufacturer's instructions and guidelines when using generators.
- Use a generator or other fuel-powered machines outside the home. CO fumes are odorless and can quickly overwhelm you indoors.
- Use the appropriate sized and type power cords to carry the electric load. Overloaded cords can overheat and cause fires.
- Never run cords under rugs or carpets where heat might build up or damage to a cord may go unnoticed.

Never connect generators to another power source, such as power lines. The reverse flow of electricity or 'back-feed' can electrocute an unsuspecting utility worker.

Follow the Incident Action Plan Safety Guidelines

Dispersion Level Chart

- Dispersion Range 0-40 is stable air, low fire intensity, less long range spotting.
- Dispersion Range 41-70 is moderate unstable air, increased fire intensity and long range spotting.
- Dispersion Range 70+ is unstable air, high amount of upper lifting, intense fire activity, potential for long range spotting and plume dominated wildfires.

Fireline Handbook Jan.'98

Fight fire aggressively, but provide for safety first.

Initiate all action based on current and expected fire behavior.

Recognize current weather conditions and obtain forecasts.

Ensure instructions are given and understood.

Obtain current information on status.

Remain in communication with crewmembers, your supervisor, and adjoining forces.

Determine safety zones and escape routes.

Establish lookouts in potentially hazardous situations.

Remain in control at all times.

Stay alert, keep calm, act decisively.

NWCG Handbook 3